

TECHNICAL DATA SHEET

SPARK 0W-20 SN Premium

Full Synthetic Long Life Engine Oil

DESCRIPTION:

SPARK 0W-20 SN Premium is a full synthetic engine oil for petrol, LPG and light diesel engines with or without turbos and catalytic converters where a Fuel Economy oil is recommended. It has been developed with special additives, which provide optimal protection during extended drain intervals. The SPARK Premium family contains four fully synthetic blends; 0W-20, 0W-30, 5W-20, and 5W-30. SPARK Premium ensures cleaner combustion, enhanced Fuel Economy (M111 test has shown over 3% of fuel saving) and low emission levels. Special additives keep the oil and engine parts free from sludge and deposits. It guarantees rapid and stable lubrication and high thermal stability under heavy duty conditions in a broad temperature range. The quality lubricant ensures an extended drain as well as low oil consumption.



- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good Anti-Wear, Anti-Corrosion and Anti-Foaming properties

TYPICAL PROPERTIES:

SAE	Unit	0W-20
Density 15°C:	Kg/m3	844
Viscosity 40°C:	cSt	44.4
Viscosity 100°C:	cSt	8.5
Viscosity Index		172
Pour Point	°C	-39
Flash Point	°C	>201



PERFORMANCE LEVELS:

- API SP
- API SP-RC
- ILSAC GF-6A
- Chrysler MS–6395
- Ford WSS-M2C-947A
- GM Dexos 1 Gen 2